



HVAC-R PRODUCT CATALOG

A large, close-up, black and white photograph of a circular HVAC fan grille, showing the concentric rings and the central hub, serving as the background for the lower half of the catalog cover.

Condensate Management
Compressor Maintenance
Air Diffusers
Linesets & Lineset Covers
Locking Refrigerant Caps
Equipment Mounting
Specialty Chemicals
Air Conditioning Chemicals
Heating Chemicals



RECTORSEAL™

AUSTRALIA



POLYSLAB **EVO-CRETE**

Our ultra-lightweight **Polyslab & Evo-Crete** equipment bases now have a supporting cast of their own...

Introducing **Acid Away®** for POE.

Neutralize acids - the primary cause of A/C compressor burnout.

- Restore PH balance and A/C performance immediately.
- Specially formulated for both hermetic or semi-hermetic compressors that operate with polyolester oils.
- Tested to various ASTM standards and ANSI/ASHRAE 86-1983 and 97-1989
- Non-toxic - safe and easy to use.
- No flushing needed.






AC BLOCKS - COMPLETE MOUNTING KIT

THE LIGHT WEIGHT DURABLE PVC ALTERNATIVE



Complete kit weighs
ONLY 8 KG



Kit includes: **2x** Evo-Crete AC Blocks **4x** Anti-Vibration Rubber Mounts **4x** Stainless Steel Evo-Crete Screws **4x** Stainless Steel Washers

What is Evo-Crete?

Evo-Crete is a dynamic, Ultra Lightweight Cellular Concrete – 3 times lighter than standard concrete. Evo-Crete is highly reinforced with a proprietary blend of several different polyolefin fibres offering superior strength to weight properties, durability and quality over current heavy concrete, polystyrene filled and foam blended concrete products on the market



OR



- *Evo-Crete will outlast PVC supports EVERYTIME!*

Evo-Crete will not be affected by harsh UV rays or weather and will not break down and become brittle over time.

- *Evo-Crete looks, feels and IS a superior product*

Resulting in a quality finish that your customers will appreciate.

- *Evo-Crete's solid design will not harbour unwanted pests*

Hollow PVC products offer refuge for spiders, rats, ants and snakes.

- *Evo-Crete is easy to use. No wasted time lining up bolts, nuts & washers*


Simply screw down in any location with the Evo-Crete screws supplied (no pre-drilling required)



Suit most applications



Versatile



Simple Installation



Working with Evo-Crete


Evo-Crete can be fabricated and modified with basic hand or power tools and can easily be cut & shaped to fit any application. Almost any equipment can be attached to Evo-Crete with the use of specialised Evo-Crete fixtures, no pre-drilling required (fixtures included in all AC Block Complete Mounting Kits). Dyna bolts and traditional concrete fastening methods can be used if required.



Evo-Crete Pre-Cast Slabs

| Square Slabs – Flat | Available Sizes (mm) | Weight (Kg) |
|--|--------------------------|-------------|
|  <p>Designed as a stable equipment base for: Hot Water Systems, Generators, Gas Bottles, Pool Pumps and Filters, Irrigation pumps, and more.</p> | 450x450x50 600x600x50 | 8.5 14.5 |

| Rectangular Slabs – Flat | Available Sizes (mm) | Weight (Kg) |
|---|----------------------|-------------|
|  <p>Designed as a stable equipment base for: Hot Water Systems, Generators, Air-Conditioners, Gas Bottles, Pool Pumps and Filters, Irrigation pumps, and more.</p> | 900x450x50 | 16.0 |

| 'Ripple Top' Slabs | Available Sizes (mm) | Weight (Kg) |
|---|----------------------|-------------|
|  <p>Specifically designed to meet Plumbing Code AS/NZ3500.4. Great for any application where pooling of water is not desirable.</p> | 600x600x50 | 14.5 |



POLYSLAB[®]



AUSTRALIA'S MOST **TRUSTED** EQUIPMENT BASE

Polyslab is the product of choice across a variety of industries. Durable, stylish, easy to use and proudly 100% Australian made and owned.



SUITABLE FOR
INSTALLATION
ON ANY SURFACE
(Install guide)



GREAT FOR AIR-CONDITIONERS, GENERATORS, PUMPS & MORE

AVAILABLE IN:

| | |
|--------|--|
| LARGE | 1130 x 650 x 51mm - 6.5kg (Load rating to 160kg) |
| MEDIUM | 885 x 465 x 51mm - 2.4kg (Load rating to 160kg) |
| SMALL | 640 x 340 x 51mm - 1.6kg (Load rating to 120kg) |

Patent and Registered Design Details

317165, 331871, 313328, 2008291692 &




POLYSLAB EQUIPMENT BASES

AUSTRALIA'S MOST TRUSTED EQUIPMENT BASE

Detailed structural engineering, design and analysis continues to be fundamental to our approach in maximising the strength-to-weight ratio of the entire Polyslab range. Our rectangular equipment bases are available in three sizes to suit all split system air conditioning units as well as generators, pumps and various other types of equipment.

Polyslab equipment bases are built to stand the test of time and are guaranteed to outlast the equipment they support. Polyslab is the easy, smart, stylish and environmentally friendly choice - why would you use anything else?

UNDERSIDE VIEW



PERIMETER SUPPORT

Combined with the channel supports gives the greatest possible surface area support.

MULTIPLE CHANNEL SUPPORTS

Transfer weight of the unit directly to the ground to prevent sinking. Design also allows products to 'lock in' and stack easily for transport.

UNDERSIDE RIBS

The location, thickness and depth have been designed to maximise strength.

ULTRA LIGHTWEIGHT

All Polyslab Bases replace heavy, cumbersome, and often fragile pre-cast concrete slabs. Avoid injuries and OH&S litigation with the durable, stylish, lightweight alternative.

INSTALLATION

POLYSLAB BASE: Flat Surface

As with any equipment base, the quickest and easiest install for a Polyslab is on an existing flat level surface (e.g. concrete or compacted earth). For maximum stability, it is recommended that the equipment is fixed down to the Polyslab base (e.g. screw straight into Polyslab with self-tapping screws or pre-drill & bolt).

POLYSLAB BASE: Uneven Surface

These steps are strongly recommended for increased stability on loose, unfirm or uneven surface. If existing uneven surface is loose enough, smooth out with the edge/base of the Polyslab. If existing uneven surface is compacted, place a mound of loose soil, gravel or other suitable material on top, level out with the edge/base of the Polyslab. Lay Polyslab in place and ensure the product is level with a firm footing. For maximum stability, it is recommended that the equipment is fixed down to the Polyslab base (e.g. a screw straight into Polyslab with self-tapping screws or pre-drill & bolt).

Condensate Management

- Drain Hoses
- Safe-T-Switch®
- EZ Trap®
- AquaGuard®
- Condensate Pans and Risers
- Drain Line Cleaners
- Mighty Pump™



SAFE-T-SWITCH®

The Most Reliable Switch


- **Magnetic Reed Switch**
- **Easy to Install & Service**
- **Code Compliant**
- **UL Listed 508**
- **Installation on Primary & Auxiliary Drain Outlets or Pans**
- **Adjustable Bracket SS4
Normally Open SS3CT**
- **Electronic Probe Sensors
SS103E & SS500EP**
- **Introducing New sensor for:
Mini split units - SS 610E
Universal Puck - SS 700E**



SAFE-T-SWITCH®

Safe-T-Switch® is the most reliable condensate overflow switch available. It detects clogged air conditioning condensate drains and shuts off the system to prevent water damage to the structure.

This easy to install, uniquely designed, patented magnetic reed switch will not stick or rust. Safe-T-Switch® condensate overflow switch can be connected to either the red or yellow (thermostat) wires.



Model SS1

For Installation on Primary Drains or Auxiliary Drain Outlets

Safe-T-Switch® model SS1 can be installed horizontally or vertically, inline or on the primary pan's auxiliary drain outlet by using the included $\frac{3}{4}$ " adapter, bushing and cap. It can be installed on a sloping line and does not need to be level or plumb.

| RS # | Description | Qty |
|-------|-------------|-----|
| 97632 | Model SS1 | 24 |



Model SS2

For Installation on Primary Pan Auxiliary Outlet

Using the $\frac{3}{4}$ " adapter, the SS2 can be installed on the auxiliary outlet of the primary drain pan. The SS2 also provides easy access to the switch and the primary drain line for service.

| RS # | Description | Qty |
|-------|-------------|-----|
| 97637 | Model SS2 | 24 |




Model SS3

For Installation on Primary & Auxiliary Drain Pans

The specially designed steel mounting bracket clips firmly over the edge of most drain pans. The slim-profiled SS3 can be installed on primary or auxiliary drain pans.

| RS # | Description | Qty |
|-------|-------------|-----|
| 97647 | Model SS3 | 24 |





Which Safe-T-Switch is Right for You?

| Model # | RS # | Float Switch | Electric Probe | Drain Line Primary | Drain Line Secondary | Drain Pan | Ductless Mini Split | Normally Open | Normally Closed | Plenum Rated | UL-508 | UL-2043 |
|----------|-------|--------------|----------------|--------------------|----------------------|-----------|---------------------|---------------|-----------------|--------------|--------|---------|
| SS1 | 97632 | ✓ | | ✓ | ✓ | | | | ✓ | | ✓ | |
| SS2 | 97637 | ✓ | | | ✓ | | | | ✓ | | ✓ | |
| SS3 | 97647 | ✓ | | | | ✓ | | | ✓ | | ✓ | |
| SS4 | 97625 | ✓ | | | | ✓ | | | | | ✓ | |
| SS3-CT | 97652 | ✓ | | | | ✓ | | ✓ | ✓ | | ✓ | |
| SS2AP | 97640 | ✓ | | | ✓ | | | | ✓ | ✓ | ✓ | ✓ |
| SS103 E | 97692 | | ✓ | ✓ | ✓ | ✓ | | | ✓ | | ✓ | |
| SS500 EP | 97693 | | ✓ | | | ✓ | | | ✓ | ✓ | ✓ | ✓ |
| SS610 E | 97622 | | ✓ | | | ✓ | ✓ | ✓ | ✓ | | ✓ | |
| SS700 E | 97695 | | ✓ | | | ✓ | | | ✓ | | ✓ | |

Safe-T-Switch Accessories

Model SG1



SAFE-T-GARD®

Condensate Overflow Alarm

Alerts the dwelling occupant when the drain is clogged, before the house gets hot. Use with Safe-T-Switch.

| RS # | Description | Qty |
|-------|-------------|-----|
| 97655 | Model SG1 | 25 |



Condensate Drain Line Cleaners



Hydrex™ A/C Tabs

A/C Drain Pan & Drain Line Treatment

- Prevents drain line and pan blockage in air conditioners, humidifiers and refrigerators due to build up of sludge and slime.
- 2 tablets per one ton of air conditioning controls odor and sludge for up to 3 months.
- Tablets are easily dispensed from the plastic bottle.

| RS # | Description | Qty |
|-------|-------------|-----|
| 68115 | 200 tablets | 12 |



Nu Line®

A/C Condensate Drain Cleaner

- Helps prevent A/C drain line clogs and water leaks by removing slime and keeping drain lines open.
- Use every three months to help prevent mold growth in clogged A/C drain lines.

| RS # | Description | Qty |
|-------|-------------|-----|
| 97685 | 8 ounce | 24 |
| 97690 | 32 ounce | 12 |

Model SS2

Primary pan auxiliary outlet

| Code | Description | Qty. |
|-------|-------------|------|
| 97637 | Model SS2 | 24 |



FEATURES

- Condensate overflow switch
- Magnetic reed switch
- Connect to either red or yellow wire



Application

- Detects clogged A/C condensate drains and shuts off the system
- Using the 3/4" adapter the SS2 can be installed on the auxiliary outlet of the primary drain pan
- Easy access to the switch and the primary drain line for service

US Patent No. 6,442,955



Model SS3

Primary & auxiliary drain pans

| Code | Description | Qty. |
|-------|-------------|------|
| 97647 | Model SS3 | 24 |



FEATURES

- Condensate overflow switch
- Magnetic reed switch
- Connect to either red or yellow wire



Application

- Detects clogged A/C condensate drains and shuts off the system
- Steel mounting bracket clips firmly over the edge of most drain pans
- Slim profile can be installed on primary or auxiliary drain pans

US Patent No. 6,698,215



Model SS2AP

Plenum rated

| Code | Description | Qty. |
|-------|-------------|------|
| 97640 | Model SS2AP | 50 |



FEATURES

- Condensate overflow switch
- Magnetic reed switch
- Connect to either red or yellow wire



- Application**
- Detects clogged A/C condensate drains and shuts off the system
 - Schedule 40 CPVC, plenum rated and listed to UL-2043
 - Use 3/4" adapter to install on the auxiliary outlet of the primary drain pan

US Patent No. 6,442,955

SAFE-T-SWITCH® ELECTRONIC SWITCHES

SS 103 E

Dual sensors

| Code | Description | Qty. |
|-------|-------------|------|
| 97692 | SS 103 E | 24 |



FEATURES

- Electronic probe sensor
- 5-wire design
- Onboard LED indicator
- 5 amp carrying capacity

Application • For primary drain line and auxiliary drain pan or auxiliary drain outlet and auxiliary drain pan

- Can be installed horizontally or vertically or inline
- Onboard LED indicates the condition of the unit at a glance
- No moving parts



US Patent Pending

SS 500 EP

Commercial rooftop downflow units

| Code | Description | Qty. |
|-------|-------------|------|
| 97693 | SS 500 EP | 24 |



FEATURES

- Electronic probe sensor
- 5-wire design
- Onboard LED indicator
- Plenum rated wire
- 5 amp carrying capacity

Application • Install on primary drain pan when plenum rating is needed

- Small size and slim profile great for use on commercial rooftop downflow units



US Patent Pending

SS 610 E

Mini-Split systems

| Code | Description | Qty. |
|-------|-------------|------|
| 97622 | SS 610 E | 12 |



FEATURES

- Sensor connects to indoor units
- Onboard LED indicator can be mounted to side of unit
- Univolt input 15-250 Vac 15-100 Vdc

Application • Designed for mini-split systems

- For installation directly on primary drain pan or clipped to coils above primary drain pan
- Multi-voltage
- Can be wired in both normally open and normally closed systems
- No batteries required



US Patent No. 8,887,392

SS 700 E

Directly in the secondary drain pan

| Code | Description | Qty. |
|-------|-------------|------|
| 97695 | SS 700 E | 24 |



FEATURES

- Multiple mounting angles
- Works in any position
- Universal puck works in all secondary drain pans
- Onboard LED indicator
- Stainless steel bracket

Application • Designed to work in any position within a secondary drain pan, eliminating screws and clips

- Multiple position option for the sensor and provides adjustable height
- Great for use in plastic overflow pans with round edges
- Automatically resets when water drains or is removed from secondary pan



US Patent Pending

EZ TRAP® 100 SERIES CLEAR TRAP™ KITS

Clear cleanable trap.


EZ TRAP®**Condensate Traps and Overflow Switches**

Easy Maintenance & Overflow Protection

1 SmartTrap™ (200 SERIES)

adds a float switch that warns of blockage and shut down the A/C unit. Slip fit float switch removes easily for cleaning and inspection.

2 Proven reliability and higher switching capacity with microswitch technology. (4A NO/NC)



3 Transparent Trap is easy to clean and easy to inspect.

Quality construction with durable schedule 40 PVC fittings.

4 Watertight red caps provide easy access to clean the trap and drain pan outlet.

EZ TRAP

(Patent No. 5,069,042)

2 Year Warranty

RS # (ref. #)

Size

83113 (EZT113)**3/4"**

Economy trap kit no/brush
Thinner walled trap for light duty applications. 10 per carton.
Includes: 3/4" trap, 3/4" cross, 3/4" tee, three 3/4" red caps, 1" drop.

RS # (ref. #)

Size

83114 (EZT113B)**3/4"**

Economy trap kit w/brush
Thinner walled trap for light duty applications. 10 per carton.
Includes: 3/4" trap, 3/4" cross, 3/4" tee, three 3/4" red caps, cleaning brush, 1" drop.

RS # (ref. #)

Size

83119 (EZT119)**1"**

High flow commercial trap kit
for use when a 1" dia. discharge is required. 10 per carton.
Includes: 1" standard trap, 1" cross, 1" tee, 1" x 3/4" reducer bushing, 3/4" black stub, two 1" red caps, 1" male adaptor, cleaning brush, 1" drop.

RS # (ref. #)

83406 (EZT406)

Standard Cleaning Brush
18" flexible rod. 25 per carton.

RS # (ref. #)

83405 (EZT405)

Heavy Duty Cleaning Brush
18" flexible stainless rod. 10 per carton.

200 SERIES SMARTTRAP™ KITS

Float switch overflow protection. Clear cleanable trap

RS # (ref. #)

Size

83205 (EZT205)

3/4"



Deep SmartTrap kit for fluctuating static pressure found in systems with variable speed air handlers. 10 per carton.

Includes: 3/4" Deep Standard Trap, 1" cross, 1" red cap, 1"x 3/4" bushing, 3/4" tee, 3/4" black stub, 3/4" male adapter, float switch assembly, 48" cable, cleaning brush, 3" drop.



RS # (ref. #)

Size

83207 (EZT207)

3/4"



Side entry SmartTrap kit for offset mounting on "A" coil applications on top of a vertical furnace. 10 per carton.

Includes: 3/4" Standard Trap, 3/4" cross, two 3/4" red caps, 3/4" tee, 3/4" black stub, 3/4" male adapter, float switch assembly, 48" cable, cleaning brush, reducing tee, 1" drop.



RS # (ref. #)

Size

83210 (EZT210)

3/4"



Standard SmartTrap kit fits most applications requiring automatic shut down. 10 per carton.

Includes: 3/4" Standard Trap, 3/4" cross, 3/4" red cap, 1"x 3/4" bushing, 3/4" tee, 3/4" black stub, 3/4" male adapter, float switch assembly, 48" cable, cleaning brush, 1" drop.



RS # (ref. #)

Size

83230 (EZT230)

3/4"



Tamper resistant SmartTrap kit with threaded cleaning cap. Fits most applications. Includes clear u-bend for inspection, and access ports for easy cleaning. 10 per carton.

Includes: 3/4" Standard Trap, 1" cross, 3/4" locking cap, 1"x 3/4" bushing, 3/4" tee, 3/4" black stub, 3/4" male adapter, float switch assembly, 48" cable, cleaning brush, 1" drop.



220 SERIES OVERFLOW SWITCHES

Float switch overflow protection.

RS # (ref. #)

Size

83224 (EZT224)

3/4"



Compact overflow switch with 3/4" male threaded inlet. Thread into fitting on secondary drain pan. 10 per carton.

Includes: 1"x 3/4" male threaded street ell, float switch assembly, 48" cable.



RS # (ref. #)

Size

83225 (EZT225)

3/4"



Inline universal primary/secondary overflow switch

3/4" or 1" inlet, with 3/4" outlet. Install vertical or horizontal, inline or plugged. 10 per carton. Includes: 1"x 3/4"x 1" tee, 3/4" male adaptor, 3/4" plug, 1"x 3/4" bushing, float switch assembly, 48" cable.



RS # (ref. #)

Size

83226 (EZT226)

3/4"



Compact overflow switch with 3/4" female slip inlet

Two part design for use where obstructions prevent direct threading. 10 per carton.

Includes: 1"x 3/4" slip female street ell, 3/4" male adaptor, float switch assembly, 48" cable.



RS # (ref. #)

Size

83228 (EZT228)

3/4"



Inline primary/secondary overflow switch

Same as 225 with clear extension tube for visual indication. 10 per carton.

Includes: 1"x 3/4"x 1" tee, 3/4" male adaptor, 3/4" plug, 1"x 3/4" bushing, float switch assembly, extension tube, 48" cable.



EZ TRAP® 100 SERIES WATERLESS KITS

Waterless freeze protection.

EZ TRAP®



UltraTrap™ Waterless Condensate Traps

For Negative & Positive Pressure Systems
Up to .5" WG, Capacity 2.7 GPM

1 UltraTrap™

Unique patented design retains no water and needs no priming. Spring-assisted float eliminates standing water and freezing problems associated with conventional P traps. UltraTrap allows free flow of condensate while preventing reverse airflow.

2 Captive twist-off locking ring.



3 Transparent trap allows for easy cleaning and inspection.

4 Stainless steel spring.

EZ TRAP

(Patent No. 6,698,225)

2 Year Warranty

RS # (ref. #)

Size

83150 (EZT150)

3/4" OR 1"



UltraTrap waterless trap kit eliminates standing water and freezing problems. Positive or negative pressure systems. 5 per carton.

Includes: 3/4" UltraTrap, 3/4" cross, two 3/4" red caps, 3/4" male adaptor, 3/4" coupler, cleaning brush.

U. S. Patent No. 6,698,225

RS # (ref. #)

Size

83180 (EZT180)

5/8"



Mini waterless in-line trap sized for use in ductless mini-split applications. Use on any mini-split condensate drain line. Permits free condensate flow while blocking odors, noise and insects. Freeze resistant. Only 2-3/4" long. 10 per carton. Includes: 5/8" MiniTrap, 9/16" adapter.

**600
SERIES**

Combo kit Clear Trap and Overflow Switch

RS # (ref. #)

Size

83626 (EZT626)

3/4"



For coverage of the entire condensate drain system. 5 per carton.

Compact overflow switch with 3/4" female slip inlet. Two part design for use where obstructions prevent direct threading.

Includes: 1"x 3/4" slip female street ell, 3/4" male adaptor, float switch assembly, 48" cable.

Economy trap kit w/brush. Thinner walled trap for light duty applications.

Includes: 3/4" blow molded trap, 3/4" cross, 3/4" tee, three 3/4" red caps, cleaning brush, 1" drop.

CONDENSATE DRAIN LINE CLEANERS

Condensate
Management

Hydrex™ A/C Tabs

A/C drain pan & drain line treatment

| Code | Description | Qty. |
|-------|-------------------|------|
| 68115 | 200 tablet bottle | 12 |

FEATURES

- Easily dispensed
- Long lasting

Application • Prevents drain line and pan blockage in air conditioners, humidifiers and refrigerators due to build up of sludge and slime • 2 tablets per one ton of air conditioning controls odor and sludge for up to 3 months

Recommended for

- Drain pan



Compressor
Maintenance

Air Diffusers

Nu Line®

A/C condensate drain cleaner

| Code | Description | Qty. |
|-------|-------------|------|
| 97685 | 8 oz. | 24 |
| 97690 | 32 oz. | 12 |

FEATURES

- Easily dispensed
- Long lasting
- Enzyme based
- Environmentally friendly

Application • Helps prevent A/C drain line clogs and water leaks by preventing accumulation of slime and keeping drain lines open • Use every three months to help prevent mold growth

Recommended for

- Drain line • Drain pan



Linesets &
Lineset Covers

Locking
Refrigerant Caps

Actabs™

Drain line biocide

| Code | Description | Qty. |
|-------|-----------------------|------|
| 68102 | EE - 3 tab pouch | 50 |
| 68108 | 6 tablet pouch | 72 |
| 68104 | JR - 200 tab bottle | 12 |
| 68107 | DMSS - 200 tab bottle | 12 |


| | | |
|--------------|---------------------------------|----------------------|
| Actabs™ EE | Systems from 1 to 5 tons | EPA Reg. no. 51219-7 |
| Actabs™ | Systems from 6 to 15 tons | EPA Reg. no. 51219-7 |
| Actabs™ JR | All systems monthly application | EPA Reg. no. 51219-7 |
| Actabs™ DMSS | Ductless Mini-Split Systems | EPA Reg. no. 51219-7 |

Application • EPA registered biocide eliminates or prevents most blockages in air conditioning and refrigeration drain lines due to build up of bacterial slime, rust, scale, sludge, airborne dust, silt and other solids

- Lasts up to 3 months

Recommended for

- Drain pan
- Computer rooms
- Ductless Mini-Split Systems



Mounting &
Installation

Specialty
Chemicals

Air Conditioning
Chemicals

Easy Klear™

Clean-out valve

| Code | Description | Qty. |
|-------|-------------|------|
| 97585 | ¾" line | 12 |

FEATURES

- Easy upstream or downstream access to drain line

Application • Three-way clean-out valve for A/C and refrigeration condensate drain lines • Removable cap allows access for shop-vac cleaning • ¼" opening allows access to blow out clogs using CO₂ or nitrogen charges

Recommended for

- Condensate drain line



Heating
Chemicals

Other Related
Products

VACUUM OR PUSH-OUT CLOG IN CONDENSATE DRAIN LINES

Mighty Pump™

Quickly & completely clear blockage

| Code | Description | Qty. |
|-------|--------------------------------|------|
| 97795 | Mighty Pump™ | 4 |
| 97796 | Replacement Hoses 2 per bag | 6 |

FEATURES

- No nitrogen tank or gas cartridges needed
- 2-way flow w/o backflow
- Lightweight, heavy-duty molded PVC
- Easy clean up
- High volume, low pressure

Application • Hand-operated pump that can be used to vacuum or push-out a clogged drain line from inside or outside the home or building
• Generates enough pressure to clear slime, mold & dirt plugs

Recommended for

- Drain Line • A/C condensate pans • Secondary overflow pans • Water heater pans • Tubs & toilets

Includes • Pump body • Flexible hoses • Spring check valves • 3/4" adapter • Spare O-rings



Compressor Maintenance

Kickstart® •

Acid-Away® •

Acid-Away® for POE •

Acid-Detector™ •

Acid-Detector™ for POE •

Oil-ID™ •

Turbo-Kleen™ •

AC Leak Freeze™ •





A CSW Industrials Company

INTRODUCING

AC Leak Freeze® nano PRO

Stop refrigerant leaks permanently.

Restore AC performance quickly.



Dual Action Sealant

- Reliable, original, safe and polymer-free* AC Leak Freeze formula.
- With leak seeking **nano** particles.

Safe Delivery Tool

- Copper/brass construction.
- Sealant installs using standard HVAC manifold.

Triple Action Sealant

- Magic Frost adds anti-friction lubricant to reduce noise and vibration.
- System runs smoother and more efficient.



Low Loss Safety Fitting

- Connects to standard 1/4" service ports.

*Non-clogging to compressors, recovery units, schrader valves, cap tubes, TXV valves, micro channels, evacuation equipment and gauges.

AC Leak Freeze® nano PRO

| Code | AC Leak Freeze | Qty. |
|-------|------------------|------|
| 45316 | 1.46 oz nano PRO | 12 |

Leak sealant for A/C and refrigeration systems

| Code | AC Leak Freeze with Magic Frost | Qty. |
|-------|---------------------------------|------|
| 45317 | 1.46 oz nano PRO w/Magic Frost | 12 |

Leak sealant & system enhancer for A/C & refrigeration systems



Leak sealant & system enhancer



FEATURES

- Single use - disposable
- Polymer free nano formula
- Low Loss Safety Fitting
- Ready to use
- Safe for system
- Non-flammable
- Non-toxic
- OEM approved
- POP packaged
- Infuse into system using standard HVAC manifold
- Nylon hose, brass fittings and copper reservoir are all 100% recyclable.

AC Leak Freeze®

Leak sealant & system enhancer

| Code | AC Leak Freeze R - for appliance | Qty. |
|-------|----------------------------------|------|
| 45301 | .5 oz | 12 |
| 45302 | .5 oz with 1/4" adapter | 12 |

Leak sealant for appliance and refrigeration systems

| Code | AC Leak Freeze | Qty. |
|-------|--------------------------|------|
| 45311 | 1.5 oz | 12 |
| 45312 | 1.5 oz with 1/4" adapter | 12 |

Leak sealant for A/C and refrigeration systems

| Code | AC Leak Freeze with Magic Frost | Qty. |
|-------|--|------|
| 45321 | 1.5 oz | 12 |
| 45322 | 1.5 oz with 1/4" adapter & Magic Frost | 12 |

Leak sealant & system enhancer for A/C & refrigeration systems

| Code | AC Leak Freeze accessories | Qty. |
|-------|----------------------------|------|
| 45344 | 1/4" adapter only | 5 |
| 45345 | 5/16" adapter only | 5 |



FEATURES

- Polymer free
- Safe for system
- OEM approved
- Easy to use
- Non-flammable
- Non-toxic
- POP blister pack



RectorSeal® 2601 Spenwick Drive - Houston, TX 77055 800-231-3345 For further information



go to rectorseal.com



RECTORSEAL

A CSW Industrials Company

ACID-AWAY[®]
PRO

CAUTION! Combustible

Compressor
Parts Safe

NEW! Ready to use delivery method.

Compressor Burnout Acid Neutralizer

- Quick & easy to inject
- Disposable injector
- Safe for all oils
- Compressor parts safe
- Contractor preferred
- Same proven, chemical formulation

A Quick & Unique solution

to removing and preventing
acid buildup
in A/C and
refrigeration
systems.



Acid-Away® PRO

Compressor Burnout Acid Neutralizer



| Code | Description | Qty. |
|-------|----------------|------|
| 45016 | Acid-Away® PRO | 12 |

FEATURES

- Quick & easy to inject
- Disposable injector
- Compressor parts safe
- No harmful effects
- Tested to ASHRAE standards 86-1983 & 97-1989 by premier independent testing institute

Application • Chemical treatment for use in air conditioning and refrigeration systems that have experienced a burnout, or operating systems that are showing buildup in acid content • Acid-Away PRO quickly circulates throughout the system and chemically neutralizes acids that are always left in air conditioning or refrigeration systems after a burnout occurs • Once neutralized, the acid can no longer continue developing corrosion impeding it from causing another burnout to the system

Recommended for • Air conditioning and refrigeration systems • Safe for all oils



Mini-split installation is now a **single** person job!

Mighty Bracket™

Mini-split Installation Support Tool



Please contact
RectorSeal Australia
for further details
or for your local
stockist.



Patent Pending

- Clips to mini-split mounting plate, securely holding unit as connections are made. Unclips easily as unit is mounted.



- Versatile level setting adjusts to any mounting plate.



- Non-marking pads won't harm walls.



- Collapses into storage tote bag.



Mighty Bracket™

Mini-split installation support tool

| Code | Description | Qty. |
|-------|-------------------------|------|
| 97705 | Mini-split support tool | 4 |


FEATURES

- Allows single person installation
- Simple clip on support
- Does not damage walls.
- Use on all brands of mini-splits

Application • Hook onto mini-split mounting plate to hold mini-split unit securely in place while installing refrigerant lines, condensate line and electrical hookup.

User Instructions: 1. Attach Mounting Hooks of Mighty Bracket to the mini-split mounting plate tabs. (If no tabs are present on the mounting plate, Mighty Bracket hooks can be attached by screws threaded into the wall stud.) 2. Place Foot Supports flat against the wall. (If necessary to avoid potential wall scratching, place clean towel or cardboard between support foot and wall surface) 3. Position Level Adjustment Pins to make Support Arm of the brackets horizontal. 4. Lift Gates at the end of Support Arms to make sure the unit cannot slide off. 5. Place protective Sleeve Socks over Gates to avoid scratching the unit. 6. Set unit securely onto the top of the Support Arms. 7. Connect refrigerant lines using RectorSeal® NoKink™. * 8. Connect condensate drain piping and electrical wiring. 9. Carefully lift and place the indoor unit onto top tabs of mounting plate. 10. While ensuring unit does not fall, carefully remove Mighty Bracket and installation is complete.

* When paired with RectorSeal® NoKink™ Mighty Bracket™ allows simple installation without damaging or kinking copper refrigerant lines.



RECTORSEAL

A CSW Industrials Company

PRO-Fit™

FLARING & SWAGING KITS

Solutions For HVAC Fittings.



PRO-Fit™ Swage Kit

- **Precision flaring & swaging**
in seconds!
- **Burnishes surface**
reducing risk of LEAKS!
- **Durable see-through case**
for better tool visibility
- **Sold as tool box kit**
for easy transportation
- **5 bits per flare kit**
6 bits per swage kit
- **Color coded bits**
for Easy ID



PRO-Fit™ Flare Kit

| Code | Description | Qty. |
|-------|--------------------|------|
| 87001 | PRO-Fit™ Flare Kit | 4 |
| 87011 | PRO-Fit™ Swage Kit | 4 |

FEATURES

- Stopper ensures a consistent length of the flare/swage surface
- Tip guides the bit into the tube & forms a standard 45° flare or consistent swage
- Standard 1/4" Hex Shank fits directly into most power tools without adapter
- Color coded hex bits for easy ID
- Available in flare or swage bits
- Comes in a durable see-through case for better tool visibility

Application • Creates precise and fast standard 45° flare or swage in copper and aluminum line sets for Mini-split HVAC units • The spinning hex flare bit forms a standard 45° flare, and the hex swage bit forms a consistent swage without splits, burrs, blemishes or uneven edges that typically cause fitting connection leaks

Recommended for • Copper & aluminum line sets • Mini-split HVAC units • Any application requiring a 45° flare

PRO-Fit™ Flare
Copper Flare



PRO-Fit™ Swage
Copper Swage





KICKSTART® ORIGINAL 2-WIRE HARD START DEVICE

The only OEM tested & approved device.

Kickstart®

Potential relay & start capacitor

| Code | Description | Qty. |
|-------|-------------|------|
| 96506 | KS-1 | 20 |
| 96503 | TO-5 | 20 |



FEATURES

- 2-wire design for easy installation
- 3-year warranty
- Extend the life of compressors
- OEM tested & approved

Application • 2-wired starting device that uses a mechanical potential relay & start capacitor • Assists compressors in starting under very adverse conditions such as low voltage or high head pressures, extending the life of compressors by providing the correct torque to bring them up to full speed more quickly and efficiently

Recommended for • Single phase 208V, 230V, and 265V A/C, refrigeration and heat pump compressors

- KS-1 handles 3.5 - 5.0 ton
- TO-5 handles 1.0 - 3.0 ton



Condensate Management

Compressor Maintenance

Air Diffusers

Linesets & Lineset Covers

Locking Refrigerant Caps

Mounting & Installation

Specialty Chemicals

Air Conditioning Chemicals

Heating Chemicals

Other Related Products



ACID-AWAY® COMPRESSOR ACID NEUTRALIZER

Recommended by compressor manufacturers and proven to neutralize acid after burnouts.

Acid-Away®

Compressor burnout acid neutralizer

| Code | Description | Qty. |
|-------|-------------|------|
| 45004 | 4 oz. | 12 |

FEATURES

- Stays active in the system to prevent any future acid
- Great for preventive maintenance
- Safe for system components
- Tested to ANSI/ASHRAE standards 86-1983 & 97-1989
- Approved & recommended by OEM's
- More effective than claimed neutralizers or scavengers

Application • Chemical treatment for A/C and refrigeration systems that have experienced a burnout or operating systems that are showing a buildup in acid content • Protects from future burnouts • Neutralizes acid molecules, unlike other products which merely coagulate to be caught in the filter drier

Recommended for • Specifically formulated for both hermetic or semi-hermetic compressors that operate with standard CFC or HCFC refrigerants using mineral oil or alkybenzene type refrigeration oils



Acid-Away® for POE

Acid neutralizer for POE oils

| Code | Description | Qty. |
|-------|-------------|------|
| 45009 | 4 oz. | 12 |

FEATURES

- Removes residual acid
- Compatible with Polyol Ester lubricants
- Great for preventative maintenance
- Tested to ANSI/ASHRAE standards 86-1983 & 97-1989
- Approved & recommended by OEM's

Application • Prevents compressor burnouts by removing the acid buildup that can occur in Polyol Ester refrigeration oils used in A/C and refrigeration systems • Neutralizes acid molecules, unlike other products which merely coagulate to be caught in the filter drier

Recommended for • Specifically formulated for compressors that operate with Polyol Ester oils & is safe for use in all oils



Condensate Management

Compressor Maintenance

Air Diffusers

Linesets & Lineset Covers

Locking Refrigerant Caps

Mounting & Installation

Specialty Chemicals

Air Conditioning Chemicals

Heating Chemicals

Other Related Products



ACID-DETECTOR™ & OIL-ID™

Field test kits to detect acid & determine oil types.

Acid-Detector™

Test kit

| Code | Description | Qty. |
|-------|-------------|------|
| 45002 | Kit | 12 |

FEATURES

- Fast acting

Application • Test kit designed for use in the field to detect acid in air conditioning and refrigeration oils

- Quickly detects the smallest trace of acids

Recommended for

- Mineral Oil • Alkylbenzene type refrigeration oil



Acid-Detector™ for POE

Test kit for POE oils

| Code | Description | Qty. |
|-------|-------------|------|
| 45006 | Kit | 12 |

FEATURES

- Fast acting

Application • Test kit designed for use in the field to detect acid in Polyol-Ester type oil • Quickly detects unacceptable amounts of acid

Recommended for

- POE air conditioning & refrigeration oil



Oil-ID™

Identify oil type

| Code | Description | Qty. |
|-------|-------------|------|
| 45001 | Kit | 12 |

FEATURES

- Cost effective
- Quick & easy to use

Application • Field test kit quickly and easily identifies the type of refrigeration oil used in HVAC-R systems • This inexpensive product will tell you within seconds, if the oil being used is a Polyol-Ester (POE) oil or not

Recommended for

- All types of oil



Speciality Chemicals

- Thread Sealants •
- Solvent Cements •
- Soldering Fluxes •
- Metacaulk® Firestop •
- Misc. Sealants •





RECTORSEAL® THREAD SEALANTS

The finest thread sealants in the industry formulated by our highly-skilled chemists

RectorSeal® No. 5®

Multi-purpose pipe thread sealant

| Code | Description | Qty. |
|-------|-------------|------|
| 25790 | 1-¾ oz. | 24 |
| 25631 | ¼ pt. | 24 |
| 25551 | ½ pt. | 24 |
| 25431 | 1 pt. | 12 |
| 25300 | 1 qt. | 12 |
| 25271 | 1 gal. | 4 |
| 25191 | 5 gal. | 1 |
| 25112 | 55 gal. | 1 |



LISTED
PIPE JOINT
COMPOUND
MH12259

FEATURES

- Soft set / Slow drying
- Lead free
- Smooth application
- 2 year shelf life
- Certified to NSF/ANSI 61-G & 372

Application • Lubricates and protects threaded pipe and fittings
• Can be pressurized immediately up to 100 psi for piping up to 2" diameter • Ideal for a wide variety of fluids and gases including potable water

Recommended for • Galvanized Steel • Iron • Brass
• Copper • Aluminum • Stainless Steel • Polyethylene
• RTRP • PVC



Also available in
55 gal. container

No. 5® Sub-Zero

Low temperature, low odor pipe thread sealant

| Code | Description | Qty. |
|-------|-------------|------|
| 27731 | ¼ pt. | 24 |
| 27651 | ½ pt. | 24 |
| 27541 | 1 pt. | 12 |
| 27460 | 1 qt. | 12 |
| 27371 | 1 gal. | 4 |
| 27111 | 5 gal. | 1 |
| 27222 | 55 gal. | 1 |



FEATURES

- Low temperature application -35°F
- All weather formula
- Lead free

Application • Odorless, non-staining, low temperature application • Brushable to -35°F • Can be pressurized immediately

Recommended for • Galvanized Steel • Iron • Brass • Copper
• Aluminum • Stainless Steel • Polyethylene • RTRP • PVC



See ordering chart
for container sizes
available.

Condensate
Management

Compressor
Maintenance

Air Diffusers

Linesets &
Lineset Covers

Locking
Refrigerant Caps

Mounting &
Installation

Specialty
Chemicals

Air Conditioning
Chemicals

Heating
Chemicals

Other Related
Products

RECTORSEAL® THREAD SEALANTS

Continued

RectorSeal® T plus 2®

PTFE enriched pipe thread sealant

| Code | Description | Qty. |
|-------|-------------|------|
| 23710 | 1-¾ oz. | 24 |
| 23631 | ¼ pt. | 24 |
| 23551 | ½ pt. | 24 |
| 23431 | 1 pt. | 12 |
| 23391 | 1 qt. | 12 |
| 23271 | 1 gal. | 4 |
| 23191 | 5 gal. | 1 |
| 23112 | 55 gal. | 1 |

Application • Contains PTFE & synthetic fibers for superior performance • Can be pressurized immediately following application

Recommended for

- Galvanized Steel
- Iron • Brass • Copper
- Aluminum
- Stainless Steel
- Polyethylene • RTRP
- PVC • CPVC • ABS

Also available in
55 gal. container



LISTED
PIPE JOINT
COMPOUND
MH12259

FEATURES

- Non-setting
- Lead free
- 2 year shelf life
- Certified to NSF/ANSI 61-G & 372

RectorSeal® Tru-Blu™

Vibration resistant pipe thread sealant

| Code | Description | Qty. |
|-------|-------------|------|
| 31780 | 1-¾ oz. | 24 |
| 31631 | ¼ pt. | 24 |
| 31551 | ½ pt. | 24 |
| 31431 | 1 pt. | 12 |
| 31300 | 1 qt. | 12 |

Application • For high vibration environments such as refrigeration and industrial applications

- Designed for sealing vibration prone NPT connections

Recommended for

- Galvanized Steel • Iron • Brass • Copper
- Aluminum • Stainless Steel
- PVC • Polyethylene
- Reinforced fiberglass



FEATURES

- Fast drying / Flexible set
- Contains PTFE
- Lead free
- 2 year shelf life
- Certified to NSF/ANSI 61-G & 372

RectorSeal® No. 7

Corrosive chemical pipe thread sealant

| Code | Description | Qty. |
|-------|-------------|------|
| 17432 | 1 pt. | 4 |

FEATURES

- Soft Set
- Lead free

Application • Slow drying sealant for use with lines carrying corrosive chemicals: diluted acids, caustics and other chemical solutions

Recommended for

- Galvanized Steel • Iron
- Brass • Copper • Aluminum • Stainless Steel





RECTORSEAL® SOLDERING

Nokorode® Regular

Multi-purpose paste flux

| Code | Description | Qty. |
|-------|----------------|------|
| 14000 | 1.7 oz. | 48 |
| 14010 | 4 oz. | 24 |
| 14020 | 8 oz. tool box | 24 |
| 14030 | 1 lb. | 12 |



FEATURES

- Lead Free
- Cleans & fluxes all at one time
- Safe for potable water systems
- Certified to NSF/ANSI 61-G & 372
- Meets O-F-506 Type 1A & A-A-51145, MIL-F-4995-2 specs

Application • All purpose, soft soldering paste flux with a special oil base that protects the solder against corrosive attack

- Non-aggressive formula. Ideal for copper and brass fittings

Recommended for

- All solder alloys including 95/5 and lead free



Rectorshield™

Heat absorption paste

| Code | Description | Qty. |
|-------|-------------|------|
| 83554 | 11 oz. tube | 24 |

FEATURES

- Biodegradable
- Odorless

Application • A heat absorption paste to help prevent damage to sensitive controls, valves, plastic faucet parts, equipment and other soldered connections

- Reduces heat transfer by absorbing thermal energy from heat and flames

Recommended for

- Copper
- Other types of metal pipe



Open Mesh Sandcloth

| Code | Description | Qty. |
|-------|-------------|------|
| 61760 | 5 yd. | 50 |
| 61759 | 10 yd. | 50 |
| 61758 | 25 yd. | 20 |

FEATURES

- Reuseable
- 100% waterproof
- Tear-resistant nylon backing

Reuseable waterproof abrasion

Application • A premium abrasive, waterproof material with top quality performance

- If the material becomes loaded with fillings, simply rinse in water and tap out.

Recommended for

- Copper





RECTORSEAL® MISC. SEALANTS

RectorSeal® RS 136

Fireblock / smoke seal caulk

| Code | Description | Qty. |
|-------|--------------------|------|
| 66408 | 10.3 oz. cartridge | 12 |



FEATURES

- Easy application
- Interior applications only
- Water clean-up

Application • General purpose, residential acoustical fireblock

Recommended for

- Electrical • Plumbing • Plastic pipe
- Telephone communication systems penetrations



RectorSeal® Silicone Sealant

General purpose

| Code | Description | Qty. |
|-------|-----------------------|------|
| 57505 | 10.3 oz. tube - white | 12 |
| 57506 | 10.3 oz. tube - clear | 12 |

FEATURES

- Remains flexible
- Vibration resistant
- Indoors/outdoor

Application • Ideal for general sealing
• Dries to touch in 30 minutes and fully cures in 24 hours

Recommended for

- Around electrical panels • Windows • Doors
- Pipes/vents • Corner joints • Aluminum siding
- Other interior / exterior building materials



RectorSeal® Hi-Temp™

100% RTV silicone caulk

| Code | Description | Qty. |
|-------|--------------------|------|
| 57500 | 10.1 oz. cartridge | 24 |

FEATURES

- One component
- USDA specs for use in federally inspected meat and poultry plants
- F.D.A. reg #21 CFR 177.2600
- TT-S-001543A (COM-NBS) Class A
- TT-S00230C (COM-NBS) Class AA
- MIL-A-46106B Amend 3, Type 1
- Canadian 19-GP-9MA, Type 1

Application • Cures to a strong durable resilient rubber

Recommended for • Glass • Clean metal • Most types of non-oily wood • Vulcanized silicone rubber • Silicone resins
• Natural and synthetic fiber • Ceramic • Paper
• Many painted and plastic surfaces



Condensate Management

Compressor Maintenance

Air Diffusers

Linesets & Lineset Covers

Locking Refrigerant Caps

Mounting & Installation

Specialty Chemicals

Air Conditioning Chemicals

Heating Chemicals

Other Related Products

Air Conditioning Chemicals

- Coil Cleaners •
- Leak Locators •
- Cleaners & Treatments •
- Cooling Tower Treatments •
- Evaporative Cooler Treatments •



Con-Coil™

Foaming acid coil cleaner

| Code | Description | Qty. |
|-------|-------------|------|
| 82622 | 1 gal. | 4 |
| 82624 | 5 gal. | 1 |
| 82628 | 55 gal. | 1 |

FEATURES

- Removes contaminants
- Brightens as new

Application • Adhering foam lifts insulating contaminants & dulling oxide film in less than 5 minutes

Recommended for

- Finned air-cooled condenser coils
- Electronic air filters • Aluminum • Copper



Renewz™

Foaming non-acid coil cleaner

| Code | Description | Qty. |
|-------|----------------|------|
| 82644 | 1 gal. | 4 |
| 82646 | 5 gal. | 1 |
| 82650 | 55 gal. | 1 |
| 82652 | 14 oz. aerosol | 12 |

FEATURES

- High foaming
- Brightener

Application • Leaves aluminum bright, shiny and clean in less than 5 minutes

- Loosens material in hard-to-reach places

Recommended for

- Air-cooled condenser coils • Aluminum
- Cooking grease • Electronic air filters



Coil-Rite™

Evaporator coil cleaner

| Code | Description | Qty. |
|-------|-------------|------|
| 82612 | 1 gal. | 4 |
| 82614 | 5 gal. | 1 |
| 82618 | 55 gal. | 1 |

FEATURES

- Non-acid
- Non-flammable

Application • Self-rinsing cleaner and degreaser • Lifts grime and oil from normally inaccessible places

Recommended for

- Evaporator and condenser coils • Air conditioning and air handling equipment
- Electronic & permanent air filters



Foam-A-Coil™

Foaming condenser & evaporator coil cleaner

| Code | Description | Qty. |
|-------|----------------|------|
| 82632 | 1 gal. | 4 |
| 82634 | 5 gal. | 1 |
| 82638 | 55 gal. | 1 |
| 82640 | 12 oz. aerosol | 12 |

FEATURES

- Non-acid
- Non-flammable

Application • Foaming biodegradable cleaner and degreaser • Lifts grime and oil from normally inaccessible places

Recommended for

- Evaporator and condenser coils • Air conditioning and air handling equipment
- Electronic & permanent air filters





LEAK LOCATORS

Detect gas leaks in pipes or tank systems.

Better Bubble™

Gas leak locator

| Code | Description | Qty. |
|-------|------------------------|------|
| 65554 | 8 oz. - dauber top | 12 |
| 65432 | 32 oz. - trigger spray | 12 |
| 65273 | 1 gal. | 4 |



FEATURES

- Fast acting
- Long lasting
- Easy to see bubbles
- Continuous bubbling

Application • Thick formula pinpoints the smallest natural gas, LPG and A/C refrigerant leaks with well defined elastic bubbles that stand up under pressure and windy conditions • Use on surface temperatures from 20°F to 250°F

Recommended for • All types of pipe, tubing, valves, tanks, pressure vessels, condenser / evaporator coils, refrigeration coils, and many other similar applications



*FBC™ "System Compatible" indicates that this product has been tested, and is monitored on an ongoing basis, to assure its chemical compatibility with FlowGuard Gold®, BlazeMaster® and Corzan® pipe and fittings.

**FBC™, FlowGuard Gold®, BlazeMaster® and Corzan® are licensed trademarks of the Lubrizol Corporation.

RectorSeek™ Low-Temp

Low temperature leak locator

| Code | Description | Qty. |
|-------|----------------------|------|
| 61554 | 8 oz. dauber top | 12 |
| 61434 | 16 oz. trigger spray | 12 |
| 61273 | 1 gal. | 4 |
| 61111 | 55 gal. | 1 |

FEATURES

- Longer bubbling action
- Dauber or spray application
- Easy to apply

Application • Leak locator for use on pipes or tanks containing gases at low temperatures • Effective from -35°F to 200°F

Recommended for • Pipes*, tubing, valves, cylinders, tanks, pressure vessels, condenser / evaporator coils, refrigeration coils and many other similar applications

*Call Technical Services for compatibility with plastic pipes.



RectorSeek™ Mid-Temp

Normal temperature leak locator

| Code | Description | Qty. |
|-------|----------------------|------|
| 60554 | 8 oz. dauber top | 12 |
| 60434 | 16 oz. trigger spray | 12 |
| 60273 | 1 gal. | 4 |
| 60111 | 55 gal. | 1 |

FEATURES

- Longer bubbling action
- Dauber or spray application
- Easy to apply

Application • Leak locator for use at normal temperature on pipe or tanks that contain gases • Can be used on oxygen, air or gas at temperatures between 40°F to 200°F

Recommended for

• All types of pipe, tubing, valves, cylinders, tanks, pressure vessels, condenser / evaporator coils, refrigeration coils and many other similar applications



Desolv™

Mini-split Evaporator Coil Cleaning Kit

Protect interior walls & floors from damage.



Drain Pail

One Gallon Desolv evaporator coil cleaner.

SINGLE-USE ONLY

Wedge Sheets

Two single-use only Funnel Bags

Frame Support

Desolv™ Cleaning Kit

Mini-split Evaporator Coil Cleaning Kit

| Code | Description | Qty. |
|-------|---------------------------------------|------|
| 82560 | Desolv Kit / 2 single-use Funnel Bags | 1 |
| 82562 | Single-use Funnels Bags | 10 |

Kit Contents

- Desolv Cleaning Solution (1 gal.)
- C-Band Frame Assembly
- Single-use Funnels Bags (2)
- Wedge Sheets (2)
- Cleaning Brush (1)
- Drain Pail (5 gal)
- Installation Instructions

Application • Use to deep clean the indoor evaporator of mini-split A/C units that are located in areas where wall and floor protection are necessary. Kit is reusable. The replacement Funnel Bags are for single use only. Desolv Solution and Funnel Bags are also sold separately.



U.S. Patent No. 6,863,116 Under license from Crossford International LLC

Desolv™

Mini-split Evaporator Coil and Blower Fan Cleaner.

| Code | Description | Qty. |
|-------|----------------------------|------|
| 82565 | Desolv Solution (1 gallon) | 6 |

Additional Features • Completely biodegradable formula presents very little hazard to people, animals, aquatic life, and vegetation. Unlike strong acid and alkaline coil cleaners, this heavy duty product will not chemically attack (corrode) coils, surrounding metal, other non-electrical HVAC equipment components or application equipment.

Application • Powers off dirt and build up from air conditioning, refrigeration and heat pump coils safely and effectively. • Reduces energy cost by increasing the efficiency of the A/C system.



Through the use of current technology and social media, RectorSeal provides support for all chemicals, products and tools including:

- Technical information
- Marketing materials
- Product installation training videos
- Product codes
- SDS and product data sheets.
- Trade show scheduling

HVAC-R




INNOVATIVE PRODUCTS FOR THE TRADES

rectorseal.com



Firestopping



Electrical



Plumbing

Distributed By:

RectorSeal Australian website

www.rectorseal.com.au

RectorSeal HO and administration

+617 3267 7277

alanbrady@rectorseal.com.au

Suite 3, 919-925 Nudgee Road

Banyo, QLD 4014

HVACR Supplies is RectorSeal's nationally appointed sales and technical support

+612 9975 7900

info@hvacsupplies.com.au

Unit 4/14 Rodborough Road

Frenchs Forest, NSW 2086



A CSW Industrials Company